

Parameter	Requirements	Rejection point	Acceptable with price correction	D.U (differential unit)	Price correction (minus) EURE/MT for each D.U based on Fractions pro rata
TM	%Less than 5	-	More than 5%	1%	2
ASH	%Less than 11	More than 13%	11-12%	1%	3
			More than 12-13%	1%	5
V/M	%Less than 1.1	More than 1.4%	1.1-1.4%	0.10%	0.8
S	%Less than 0.5	More than 0.7%	0.5-0.7%	0.10%	1.5
P in coke	%Less than 0.04	-	More than 0.04%	-	0.7
M10	5.5-7.5%	More than 8.5%	7.5-8.5%	1%	4
		Less than 5%	5-5.5%		
M40	82-88%	More than 90%	88-90%	1%	1.5
		Less than 80%	80-82%		
CSR	62-68%	More than 71%	68-71%	1%	2.5
		Less than 60%	60-62%		
CRI	22-28%	More than 30%	28-30%	1%	1.5
		Less than 20%	20-22%		
Na ₂ O+ K ₂ O in ash	Less than 2.1%	More than 3%	2.1-3%	0.10%	0.8
mm Size 25-80	More than 95%	More than 10%(size 0-25)	Less than 95%	1%	1.5